## **Product Specification Sheet**



Description	10µl Tips			10µl Filter Tips	
Maximum Volume	10µl			10µl	
Graduation	2µl, 10µl			2μl, 10μl	
Material	Virgin Polypropylene			Virgin Polypropylene	
Autoclavable	Yes			Νο	
Certified RNase, DNase, DNA and Pyrogen free	Yes			Yes	
Hazards Data	Health 0 Non-hazardous   Flammability 1 Flammable (Class A fire)   Reactivity 0 Non-reactive   *Consult the polymer MSDS for further information on potential hazards associated with this material.				
Production Standards & Procedures	Product is Produced under controlled environment. All personnel are capped, masked, gloved and gowned in the assembly area. Lot size is variable due to continuous molding process. Tip Filters are specifically designed to help prevent liquid bypass ,cross contamination and airborne contamination from being drawn in to the Tips, thus protecting the pipette body from contamination. This Product is manufactured to the following specifications: Magnified visual examination for flash (+0.02in).				
Low Retention Tips & Regular Tips	Low Retention Tips Minimum retention = Maximum accuracy No Silicon additives = No leaching				
	Manufactured from specially developed resins combined with high quality diamond finish mould creates super hydrophobic internal surface and ensures maximum recovery of sample yield.				
Packaging	Bulk Bulk-Sterile	Racked Racked-Sterile	Reloads Reloads-Sterile	Reloads - Filter	Individually Wrapped Tip- Sterile
Technical Drawing				Liqu	
Order in:- 10µl-S-L-F-R					11 10 -
Volume     10μi   10XL   20μl     200μi   200XL   50μl     1000μi   1000XL   100μl     10XN   20μl   20μl	Sterile S	Low Retention	Filter F	R Pe	os for erfect etting
i.e 10μl Sterile Low Retention Filter Rack Tips S=Sterile, L=Low Retention, F=Filter, B=Bulk, R=Rack, K=Reload, W=Wrapped www.accumaximum.com					