

## **Product Specification Sheet**

Accumax					
Description	1000XL Tips	1000XL Filter Tips			
Maximum Volume	1250μl	1250μl			
Graduation	200µl, 500µl, 1000µl, 1200µl	200µl, 500µl, 1000µl, 1200µl			
Material	Virgin Polypropylene	Virgin Polypropylene			
Autoclavable	Yes	No			
Certified RNase, DNase, DNA and Pyrogen free	Yes	Yes			
Hazards Data	Health 0 Non-hazardous Flammability 1 Flammable (Class A fire) Reactivity 0 Non-reactive *Consult the polymer MSDS for further information on potential hazards associated with this material.				
Production Standards & Procedures	Product is Produced under controlled environment.  All personnel are capped, masked, gloved and gowned in the assembly area.  Lot size is variable due to continuous molding process.  Tip Filters are specifically designed to help prevent liquid bypass, cross contamination and airborne contamination from being drawn in to the Tips, thus protecting the pipette body				

This Product is manufactured to the following specifications:

# Low Retention Tips & Regular Tips

#### Low Retention Tips

from contamination.

Minimum retention = Maximum accuracy No Silicon additives = No leaching

Manufactured from specially developed resins combined with high quality diamond finish mould creates super hydrophobic internal surface and ensures maximum recovery of sample yield.

Magnified visual examination for flash (+0.02in).



#### **Packaging**



Bulk










Bulk-Sterile Racked-Sterile


Racked

Reloads-Sterile

Reloads - Filter Sterile

### **Technical Drawing**





Ord	er	in:-	10	00	DXI	L-S-	<u>L-</u>	F-R	
				٦l.		_			

		Volume		Sterile	Low Retention	Filter	Packing
1	10μΙ	10XL	20μΙ	S	L		В
ı	200μΙ	200XL	50μΙ			F	R
ı	1000μl	1000XL	100µl				K
١	10XN	20μΙ					W

i.e 1000µl Long, Sterile Low Retention Filter Rack Tips

S=Sterile	, L=Low Retention	F=Filter	R=Rulk	R=Rack	K=Reload	W=Wranned
J-Jieine	, L-LOW NECETICION	, r – r iitei,	, D-Duik	, II-Nack	, K-KEIDau	, vv-vviappeu





www.accumaximum.com